



Topcoat Practical Coverage Rate by system.

Cyclospartic Topcoat Practical Coverage Rate by system.

- 1/4" Full Chip – 145 -175 sq/ft per gallon.
- 1/8" Full Chip – 125 - 150 sq/ft per gallon.
- 1/16" Full Chip – 100 - 125 sq/ft per gallon.
- Quartz -100 - 125 sq/ft per gallon.
- Hybrid and Stonebridge Series – 135 - 175 sq/ft per gallon.
- Applied as second topcoat over Full Chip – 150 - 200 sq/ft per gallon.
- Applied as second topcoat over Quartz – 100 - 150 sq/ft per gallon.

Cyclo1 Topcoat Practical Coverage Rate by system.

- Applied as second topcoat over Full Chip – 400 - 500 sq/ft per gallon.
- Applied as second topcoat over Quartz - 400 -500 sq/ft per gallon.
- Applied as second topcoat over Hybrid and Stonebridge Series – 400 - 500 sq/ft per gallon.
- Grind and Seal – Direct to Concrete - 300 -400 sq/ft per gallon.
- Grind and Seal – 2nd and additional coats – 400- 500 sq/ft per gallon.
- Medici Topcoat- 400 -600 sq/ft per gallon.
- Metallic Topcoat- 400 - 600 sq/ft per gallon.
- Solid Color Coat #2 and #3 – 400 - 500 sq/ft per gallon.

TOPCOAT CALCULATION - (SQ FT / SPREADRATE x 128 OZ = Estimated Ounces Needed)

****Coverage rate can vary depending on the texture of surface, porosity and condition of the concrete, air temperature, surface temperature, humidity during application and application method. ****